

FIPRO COLOR[®]

Elastic, final coat, fireproof paint

Standard colour: white (can be coloured)

Properties:	Water resistant, flame retardant, elastic, non-flaking and non-cracking, matt finish flameproof coating for absorbent and non-absorbent surfaces. Fipro Color[®] can be applied to a wide range of materials, including: <ul style="list-style-type: none">• Polyurethane foam• Polystyrene• Melamine resin foam• Polyester resin• Metal• Wood• Leather• Cardboard• Hard fibre board• Foils – tarpaulins etc.• Rubber (e.g. car tyres)• and many more.
Special areas of application	Suitable for outdoor use, highly weather resistant
Hazardous Substance Regulation:	Does not require labelling.
Solubility:	Can be diluted with cold water.
Storage:	Store in a cool and frost-free place.
Active agent guarantee:	Active for a minimum of 12 months when stored in a closed container.
Container sizes:	10 and 20 litre containers
Quantity required:	The quantity required depends on the type and thickness of the material (approx. 1 – 1.5 l / m ²)
Application:	Stir well; apply using a brush, roller or airless paint sprayer. Apply 1 – 2 coats depending on the surface.
Cleaning:	Clean tools with water immediately after finishing the work.
Safety precautions:	Protect face and hands (gloves, face mask, goggles) when using spraying devices. Provide sufficient ventilation when spraying high concentrations on large areas.